

# Reeves Boatbuilders

## Standard Narrowboat Steelwork Specification

- \* 10mm Base, 6mm Hull sides, 4mm Cabin & Roof
- \* Prime 43A Steel- Certificates on request

### FRAMING

- \* 80x80x6mm Floor bearers
- \* 60x60x6mm Knees- vertical on hull sides
- \* 60x60x6mm Full length hull stringers
- \* 30x30x3mm Cabin framing
- \* 25x25x3mm Box Section, cabin roof beams

### GENERAL

- \* 80x50mm Solid Skeg
- \* 50mm Solid rudder post
- \* 4 -Full length guards, 50mm welded top & bottom
- \* Integral diesel tank
- \* Vented gas locker
- \* Weed hatch, easy access through lifting hatch on back deck
- \* Engine beds to suit specified engine
- \* Keel cooling tank
- \* Self draining front & rear decks
- \* Front "T" stud & rear dollies
- \* Fully welded bow flares
- \* Permanent security number
- \* Window & vent apertures cut to suit
- \* Steel rear doors & sliding hatch
- \* Centre mooring eye on roof
- \* High build phosphate primer to cabin
- \* Two pack epoxy coating to hull

All steelwork is built to comply to current requirements for BWB Boat safety and the Recreational Craft Directive.